

MANUAL FURLING SYSTEMS

> The Racing models

- > Range of 5 models for boats from 6 to 20 m.
- > Black and ovale profile.
- > Several fittings: adjustment plates, long link plates, turnbuckle cylinder, below the deck fitting.
- > Options: stainless steel locking devices.
- > 10 year world wide warranty.



Racing models	R250	R350	R420	R430	R480
Max. forestay Ø (mm)	6,35	8	10	11.1	12.7
Equivalent in # rod	# 10	# 17	# 22	# 30	# 40
Clevis pin Ø (mm)	8-10-12-14-16		10-12-14-16-19-22-25		16-18-19-22-25-28
Furling standard length (m)	8	12	14	16	18
Extrusion length (m)	2	2	2	2	2
Weight / meter Kg	0,383	0,638	0,835	0,835	1,200
Removable drum	Yes				
Feeder	Yes				
Opening prefeeder	Yes				
Double luff groove	Yes				
Luff line Ø (mm)	5 mm				6 mm
Swiveling attachment device	Yes				
Long link plates	Option				
Turnbuckle cylinder	Option				
Stainless steel devices	Option				
Warranty	10 year world wide warranty				

> How to choose my furling system?

To select properly your own furling system, refer to the following steps:

- > **Step 1:** Define your sailing program: cruising or racing-cruising.
- > **Step 2:** Measure accurately the diameter of the forestay and report to the table below.
- > **Step 3:** Choose one of the fitting systems described on page 12.

		Boat length (meter)										
Model	Max forestay Ø mm	6	7	8	9	10	11	12	13	14	16	19
R250	6.35	Yes										
R350	8				Yes							
R420	10						Yes					
R430	11.1 (rod-30)								Yes			
R480	12.7 (rod-40)										Yes	