

System with Sta-Lok™ - is designed to be easily installed on your existing standard wire headstay and turnbuckle. Complete kit includes Furler, Base Toggle/Link, Sta-Lok™ fitting and wire bearing liners*.

System without Sta-Lok™ - is designed for rod or pre-swaged wire headstays that are typically assembled by a professional rigger. Kit includes Furler, Based Toggle/Link and wire bearing liners*.

*System 750 does not utilize wire bearing liners.

Ordering Chart: System SnapFurl, 750, 1100, 2100, 3100 & 4100

System	System Sta-Lok™	Without Sta-Lok™	Boat Size	Wire Dia.	Pin Dia.	Rod Size	Sta-Lok™ Length	System Length
SnapFurl CF500	—	CF500	16' - 24' (4.9 - 7.3m)	1/8" (3mm) 5/16 (4mm) 3/16 (5mm)	1/8" (3mm) 5/16 (8mm) 3/16 (9.6mm)	—	—	31' 1" (9.5m)
SnapFurl CF-700	—	CF-700	24' - 28' (7.3-8.5m)	3/16" (5mm) 7/32" (55mm)	3/8" (9.5mm) 7/16 (12mm)	-4 (4.37mm) -6 (5.03mm)	1 3/4" (44mm) 2 1/8" (54mm) 2 1/2" (64mm)	38' (11.6m)
System 750	750-01	750-55	20'-28' (6.1-8.5m)	1/8" (3mm)	1/4" (6mm)	-	1 9/16" (40mm)	35' 11 1/4" (11m)
	750-02	750-66	20'-28' (6.1-8.5m)	5/32" (4mm)	5/16" (8mm)	-4 (4.37mm)	1 3/4" (44mm)	35' 11 1/4" (11m)
	750-03	750-77	20'-28' (6.1-8.5m)	3/16" (5mm)	3/8" (9.5mm)	-6 (5.03mm)	2 1/8" (54mm)	18' 1/2" (470m)
	750-04	750-88	20'-28' (6.1-8.5m)	7/32" (5.5mm)	7/16" (12mm)	-6 (5.03mm)	2 1/2" (64mm)	35' 11 1/4" (11m)
System 1100	1100-01	1100-44	27'-31' (8.2-9.5m)	3/16" (5mm)	3/8" (9.5mm)	-4 (4.37mm)	2 1/8" (54mm)	43' (13m)
	1100-02	1100-55	27'-31' (8.2-9.5m)	7/32" (5mm)	7/16" (12mm)	-6 (5.03mm)	2 1/2" (64mm)	43' (470m)
	1100-03	1100-66	27'-31' (8.2-9.5m)	1/4" (6mm)	1/2" (13mm)	-8 (5.7mm)	2 9/16" (65mm)	43' (13m)
	1100-04	(use 1100-66*)	27'-31' (8.2-9.5m)	9/32" (5mm)	1/2" (13mm)	-10 (6.35mm)	3" (76mm)	43' (13m)
System 2100	2100-01	2100-44	30'-42' (9.1-12.8m)	1/4" (6mm)	1/2" (13mm)	-8 (5.7mm)	2 9/16" (65mm)	49' 3" (15m)
	2100-02	(use 2100-44*)	30'-42' (9.1-12.8m)	9/32" (7mm)	1/2" (13mm)	-10 (6.35mm)	3" (76mm)	49' 3" (15m)
	2100-03	2100-55	30'-42' (9.1-12.8m)	5/16" (8mm)	5/8" (16mm)	-12 (7.1mm)	3 1/4" (83mm)	49' 3" (15m)
	2100-04	(use 2100-55*)	30'-42' (9.1-12.8m)	3/8" (9.5mm)	5/8" (16mm)	-17 (8.38mm)	3 1/4" (95mm)	49' 3" (15m)
System 3100	3100-01	3100-44	41'-55' (12.5-16.8m)	5/16" (8mm)	5/8" (16mm)	-12 (7.1mm)	3 1/4" (83mm)	64' 7 1/2" (19.7m)
	3100-02	(use 3100-44*)	41'-55' (12.5-16.8m)	3/8" (9.5mm)	5/8" (16mm)	-17 (8.38mm)	3 3/4" (95mm)	64' 7 1/2" (19.7m)
	3100-03	3100-55	41'-55' (12.5-16.8m)	7/16" (12mm)	3/4" (19mm)	-22 (9.5mm)	3 3/4" (95mm)	64' 7 1/2" (19.7m)
	3100-014	(use 3100-55*)	41'-55' (12.5-16.8m)	1/2" (13mm)	7/8" (22mm)	-30 (11.1mm)	4.58" (118mm)	64' 7 1/2" (19.7m)
System 4100	4100-01	4100-44	54'-65' (16.5-19.8m)	7/16" (12mm)	3/4" (19mm)	-22 (11.1mm)	4 5/8" (118mm)	78' 1/4" (24m)
	4100-02	4100-55	54'-65' (16.5-19.8m)	1/2" (13mm)	7/8" (22mm)	-30 (9.5mm)	4 5/8" (118mm)	78' 1/4" (24m)
	4100-03	(use 4100-55*)	54'-65' (16.5-19.8m)	9/16" (14mm)	1" (25mm)	-40 (12.7mm)	5 1/2" (140mm)	78' 1/4" (24m)