

Accessories

EN 60309 socket outlet

13640	2P+E 16 A 6 h 200-250 V~ socket outlet, IP44
13645	3P+E 16 A 6 h 380-415 V~ socket outlet, IP44



13640



13645

Indicator unit for surface mounting

13660.B	Indicator unit for E14 3c (10 W) 16x54 mm lamp, white diffuser. Supplied without lamp
13660.G	As above, yellow diffuser
13660.R	As above, red diffuser
13660.V	As above, green diffuser



13660.B



13660.G



13660.R



13660.V

Surface mounting junction boxes

13884	Surface mounting junction box, RAL 7035 grey, IP55
13884.A	As above, RAL 9001 ivory



13884



13884.A

Accessories

13900	Cable entry for ø 16-20 mm conduits, grey
13900.A	Cable entry for ø 16-20 mm conduits, ivory
Δ 13905	Coupling cable entry for side-by-side installations
13907	Gland for ø 16 mm conduits
13908	Gland for ø 20 mm conduits
13910	Coupling cable entry for side-by-side installations
Δ 13912	Gland for M16 ø 16 mm thread conduits
Δ 13913	Gland for M20 ø 20 mm thread conduits
Δ 13914	Screwed cable gland, ø 12-15 mm tightening, supplied with fixing nut
13915	Screwed cable gland, ø 20-22 mm tightening, supplied with fixing nut - IP67
Δ 13919	Seal for 13910 coupling gland
Δ 13952.A	Gland for minitrunking 20x10 mm and 30x10 mm, ivory
Δ 13954.A	Gland for minitrunking 15x17 mm and 30x17 mm, ivory
13980	6 mm ² terminal for through earth conductor
Δ 13985	Terminal block with 5 6 mm ² two-screw terminals for mounting box 13884, IP00
Δ 13990	Dividing for mounting box 13884
13661	Incandescent lamp 16x54 mm E14 3c 220 V for indicator lights 13660...
V55900	ø 14 mm screwcap, to grant total insulation according to EN 60439-1 Standard



13900



13905



13907



13908



13910



13912



13913



13914



13915



13952.A



13954.A



13919



13980



13985



13990



13661



V55900