

01980

Power unit with output 29 V d.c. 800 mA, power supply 120-230 V~ 50-60 Hz, with decoupling coil, installation on EN 50022 rails, occupies 9 modules - grey RAL 7035.

Power unit with decoupling coil.
At most 2 power units can be installed on each line.

CHARACTERISTICS.

- Power: 120-230 V~ 50-60 Hz
- Consumption:
 - 120 V: 440 mA
 - 230 V: 290 mA
- BUS output voltage: 29 V d.c. (SELV) with decoupling coil
- AUX output voltage: 29 V d.c. (SELV)
- Total max output current: 800 mA
- 9 modules of 17,5 mm

INSTALLATION RULES.

Installation should be carried out observing current installation regulations for electrical systems in the country where the products are installed. Ensure clearance around the appliance so there is sufficient ventilation. There must be no dripping or splashes of water on the appliance.

WARNING: To prevent injury, the appliance must be secured to the wall as described in the installation instructions. Above the power supply there must be a bipolar circuit breaker that is easily accessible with a contact gap of at least 3 mm.

CONFORMITY TO STANDARDS.

BT directive
EMC directive
Standards EN 60065, EN 50090-2-2.

For **MARINE** use, this device has been submitted to the following tests:
IEC 60068-2-52 - Test Kb: Salt mist, cyclic (sodium, chloride solution),
IEC 60068-2-6 - Test Fc: Vibration (sinusoidal)

This device complies with part 15 of the **FCC** Rules (with the limits for a Class B digital device). Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

