

SKYVENETIAN Aluminium slat

Order Form and Product Guide

Customer _____
 Address _____

Tel _____
 Fax _____
 Mobile _____
 Email _____

Order _____
 Quote _____
 Project Name _____
 Project Location _____
 Date _____

Are any of the blinds on this order to be installed where children under 42 months old are likely to be allowed? ² **Yes No**

Window ID	Dimension Info	Slat Options	Restraint Options	Manual Control Options <small>Please choose one only</small>			Powered Control Options	Qty
				Option 1 continuous cord ³	Option 2 Lift & Tilt			
	Type Recess ¹ Blind	Size 16 25	Free Hanging Guide Wire: Chrome Dome Brass Dome Clear Plastic Chrome Low Profile	Position: Left Right	Lift cord Position Left Right	Tilt Wand options Position: Left Right	Standard 24v Wire exit point: Left Right	
Location	Width (X)	Colour		Length (mm) ⁴: 400 500 700 1000	Cleat type OA Chromed (Default) White insert Black Insert	Length mm: 150 300 1000 Custom length	Wire Free 12v DC Switches Transformers or Controls Required: Yes ⁵ No	
	Drop (Y)			Child Safety Device	Moulded Plastic : Black Clear			
	Installation height ²			Cord Tidy Black White Brown				
				Cord Tensioner Black Grey White				

1. If recess size is specified the blind will be made X minus 10mm[3/8"] and Y minus 5mm[1/4"].
2. Installation height required for cord operated blinds. EN13120 Standards demand the distance from the floor to the bottom of the pull cord(s) shall be at least 1500mm [59 1/16"] and a cord collection device (cleat or Cord tidy) is fitted at or above this height. We can only supply blinds meeting these conditions unless the above question has been answered No.
3. Continuous cords are supplied with cord tidy child safety device as standard, please select colour. Alternatively a cord tensioner can be selected.
4. Installation height less cord length must be greater than 1500mm [59 1/16"]
5. Please fill in either the Powered Accessories Order Form or the **Wire Free** Powered Accessories Order Form as appropriate.
6. A selection of simple shapes are available, please contact Oceanair for more details.



SKYVENETIAN Aluminium slat

Order Form and Product Guide

Chain/cord Tidy

Mandatory child safety device

Colours:

White Black Brown

Used on all blinds with a looped chain/ continuous cord. Fix to an adjacent wall, keeping cords taut



Cord tensioner

Mandatory child safety device

Colours:

Black Grey White

Spring tensioned device used on all blinds with a looped continuous cord. Fix to an adjacent wall, keeping cords taut



Cleats

Mandatory child safety device

Fix to an adjacent wall. Secure cord after every operation of blind,



Cord connector

Mandatory child safety device

Colour matched to slat colour

Black Light Grey Beige

Brown Dark Grey White

Breaks under horizontal force, releasing cords,



Oceanair Wand

An aluminium rod with a hook at one end and a synthetic rubber handle with the Oceanair logo at the other

Colours:

Black Grey White

Blue Beige



Oceanair Acorn

The synthetic rubber handle with the Oceanair logo is also used as an acorn for the lift cord.

Colours:

Black Grey White

Blue Beige



Where used, the rubber handle is colour matched to slat as close as possible.

Headrail

A 25mm steel headrail is used as standard and is colour matched as close as possible using the following standard colours.

White Black Brown

Vanilla Silver

An aluminium headrail and custom painting service are both available upon request, please contact Oceanair direct for more details.