

ELECTRICAL PROPERTIES



POWER	1,5W
SUPPLY	COSTANT VOLTAGE 8-32 VDC (DRIVER ON BOARD)
PROTECTION	FUSE - POLARITY REVERSE SPIKE FILTER
DIMMABLE	YES
LIGHT SOURCE	OSRAM POWER LED
LED COLOUR	3000K, RED

bcm
BENEDETTI LIGHTING

TAMPA 40

3416/K1.5W-40



MECHANICAL PROPERTIES




IP RATE	IP66
FIXTURE	FIXED COURTESY LIGHT FOR EXTERIOR/INTERIOR
FRAME	AISI 316L
HEATSINK	SPECIAL COMPOUND
SCREEN	LENS
MOUNTING SYSTEM	SPRINGS OR SCREWS

COLOUR	3000K	BEAM	25°
CRI	>80		
LUMEN OUTPUT	140 lm		
LIGHTNESS 1mt	331 lx		
LIGHTNESS 2mt	83 lx		
LIGHTNESS 3mt	37 lx		

FINISHES

POLISHED S.STEEL
BRUSHED S.STEEL
WHITE S.STEEL



CUT OUT	27 mm (1.06in)
FRAME	40 mm (1,57in)
DEPTH	20 mm (0,79in)
REFLECTOR ADJUSTABILITY	NO