

ELECTRICAL PROPERTIES



POWER	1,5W
SUPPLY	COSTANT VOLTAGE 8-32 VDC (DRIVER ON BOARD)
PROTECTION	FUSE - POLARITY REVERSE SPIKE FILTER
DIMMABLE	YES
LIGHT SOURCE	OSRAM POWER LED
LED COLOUR	3000K, RED

bcm
BENEDETTI LIGHTING

MALIBÙ A60

3412/K1.5W-A60



MECHANICAL PROPERTIES




IP RATE	IP66
FIXTURE	FIXED DOWNLIGHT FOR EXTERIOR/INTERIOR
FRAME	AISI 316L
HEATSINK	SPECIAL COMPOUND
SCREEN	OPAL
MOUNTING SYSTEM	SPRINGS

COLOUR	3000K	BEAM	90°
CRI	>80		
LUMEN OUTPUT	140 lm		
LIGHTNESS 1mt	65 lx		
LIGHTNESS 2mt	16 lx		
LIGHTNESS 3mt	7 lx		



FINISHES

POLISHED S.STEEL
BRUSHED S.STEEL
WHITE S.STEEL



CUT OUT	48mm (1.89in)
FRAME	60 mm (2.36in)
DEPTH	16mm (0.63in)
REFLECTOR ADJUSTABILITY	NO

ELECTRICAL PROPERTIES



POWER 2W

SUPPLY COSTANT VOLTAGE 8-32 VDC
(DRIVER ON BOARD)

PROTECTION FUSE - POLARITY REVERSE
SPIKE FILTER

DIMMABLE YES

LIGHT SOURCE OSRAM POWER LED

LED COLOUR 3000K, 3000K+RED

bcm
BENEDETTI LIGHTING

MALIBÙ A75

3412/K2W-A75



MECHANICAL PROPERTIES



IP RATE IP66

FIXTURE FIXED DOWNLIGHT FOR
EXTERIOR/INTERIOR


FRAME AISI 316L

HEATSINK SPECIAL COMPOUND

SCREEN OPAL


MOUNTING SYSTEM SPRINGS

COLOUR	3000K	BEAM	90°
CRI	>80		
LUMEN OUTPUT	240 lm		
LIGHTNESS 1mt	111 lx		
LIGHTNESS 2mt	28 lx		
LIGHTNESS 3mt	12 lx		



FINISHES

POLISHED S.STEEL
BRUSHED S.STEEL
WHITE S.STEEL



CUT OUT 62mm (2.44in)

FRAME 75 mm (2.95in)

DEPTH 18mm (0.71in)

REFLECTOR ADJUSTABILITY NO

ELECTRICAL PROPERTIES



POWER	4W
SUPPLY	COSTANT VOLTAGE 8-32 VDC (DRIVER ON BOARD)
PROTECTION	FUSE - POLARITY REVERSE SPIKE FILTER
DIMMABLE	YES
LIGHT SOURCE	OSRAM POWER LED
LED COLOUR	3000K, 3000K+RED

bcm
BENEDETTI LIGHTING

MALIBÙ A85

3412/K4W-A85



MECHANICAL PROPERTIES




IP RATE	IP66
FIXTURE	FIXED DOWNLIGHT FOR EXTERIOR/INTERIOR
FRAME	AISI 316L
HEATSINK	SPECIAL COMPOUND
SCREEN	OPAL
MOUNTING SYSTEM	SPRINGS

COLOUR	3000K	BEAM	90°
CRI	>80		
LUMEN OUTPUT	460 lm		
LIGHTNESS 1mt	212 lx		
LIGHTNESS 2mt	53 lx		
LIGHTNESS 3mt	24 lx		



FINISHES

POLISHED S.STEEL
BRUSHED S.STEEL
WHITE S.STEEL



CUT OUT	73mm (2.87in)
FRAME	85 mm (3.35in)
DEPTH	31mm (1.22in)
REFLECTOR ADJUSTABILITY	NO

ELECTRICAL PROPERTIES



POWER	6W
SUPPLY	COSTANT VOLTAGE 8-32 VDC (DRIVER ON BOARD)
PROTECTION	FUSE - POLARITY REVERSE SPIKE FILTER
DIMMABLE	YES
LIGHT SOURCE	OSRAM POWER LED
LED COLOUR	3000K, 3000K+RED


bcm
BENEDETTI LIGHTING

MALIBÙ A95

3412/K6W-A95




COLOUR	3000K	BEAM	90°
CRI	>80		
LUMEN OUTPUT	610 lm		
LIGHTNESS 1mt	282 lx		
LIGHTNESS 2mt	70 lx		
LIGHTNESS 3mt	31 lx		



FINISHES

POLISHED S.STEEL
BRUSHED S.STEEL
WHITE S.STEEL



MECHANICAL PROPERTIES



IP RATE	IP66
FIXTURE	FIXED DOWNLIGHT FOR EXTERIOR/INTERIOR
FRAME	AISI 316L
HEATSINK	SPECIAL COMPOUND
SCREEN	OPAL
MOUNTING SYSTEM	SPRINGS

CUT OUT 83mm (3.27in)

FRAME 95 mm (3.74in)

DEPTH 42mm (1.65in)

REFLECTOR ADJUSTABILITY NO