

## ELECTRICAL PROPERTIES



POWER	1,5W
SUPPLY	COSTANT VOLTAGE 8-32 VDC (DRIVER ON BOARD)
PROTECTION	FUSE - POLARITY REVERSE SPIKE FILTER
DIMMABLE	YES
LIGHT SOURCE	OSRAM POWER LED
LED COLOUR	3000K, RED

*bcm*  
BENEDETTI LIGHTING

SARASOTA 40

3417/K1.5W-40



## MECHANICAL PROPERTIES




IP RATE	IP66
FIXTURE	FIXED COURTESY LIGHT FOR EXTERIOR/INTERIOR
FRAME	AISI 316L
HEATSINK	SPECIAL COMPOUND
SCREEN	LENS
MOUNTING SYSTEM	SPRINGS OR SCREWS

COLOUR	3000K	BEAM	25°
CRI	>80		
LUMEN OUTPUT	140 lm		
LIGHTNESS 1mt	331 lx		
LIGHTNESS 2mt	83 lx		
LIGHTNESS 3mt	37 lx		

### FINISHES

POLISHED S.STEEL  
BRUSHED S.STEEL  
WHITE S.STEEL



CUT OUT	27 mm (1.06in)
FRAME	40x40 mm (1,57x1,57in)
DEPTH	20 mm (0,79in)
REFLECTOR ADJUSTABILITY	NO