



Product Update

November, 2019

New Soft Attachment Blocks

RF47109, RF67109 and RF77109

Available in three sizes, Ronstan's new Soft Attachment Blocks have the highest ratio of dynamic load to sheave diameter of any block in our keelboat block range and suit a multitude of demanding applications where high static and dynamic loads are encountered.



- Fully machined aluminium cheeks and sheaves.
- Full contact, self-lubricating composite bearing running on a polished duplex stainless steel hub.
- Dyneema® SK99 soft shackle with titanium dog bone.
- Exceptional working load capacity in relation to block size. MWL from 2000kg (Series 40) to 7000kg (Series 75).

With the soft shackle open, a gentle rotation of the cheeks opens the head of the block so it can be fitted to a standing line as a snatch block. To close the block, rotate back to the closed position. A spring-loaded ball secures the assembly, with no additional external straps or bands required.



The soft shackles supplied with the Soft Attachment Blocks are a versatile accessory for any boat, and may also be ordered separately.

The new blocks will be available from Ronstan Denmark in January 2020. Product images and media release are available for download [here](#).

Part Number	Description	Sheave Diam (mm)	Max. Rope (mm)	M.W.L. (kg)	B.L. (kg)	Weight (g)
RF47109	S40 Soft Attachment Block, Single	42	12	2,000	4,000	165
RF67109	S60 Soft Attachment Block, Single	60	16	4,000	8,000	365
RF77109	S70 Soft Attachment Block, Single	75	19	7,000	14,000	753
RF7008-09	Soft Shackle, 6x95mm, Suits RF47109			2,000	4,000	14
RF7010-13	Soft Shackle, 8x135mm, Suits RF67109			4,000	8,000	30
RF7014-16	Soft Shackle, 10x165mm, Suits RF77109			7,000	14,000	77