



- ✓ The lead block on RC73234 and RC73235 articulates for ideal sheet alignment and have an integrated anti-clatter rubber buffer.
- ✓ RC73231, RC73234 Jib sheet leads suit boats to 12m (40ft).

- ✓ RC73235 Jib sheet leads suit boats to 10m (33ft).
- ✓ RC73231 genoa car can accommodate two sheets for easy headsail changes, and has a plunger stop that can be locked in the "up" position.

- ⊕ Grade AL6061-T6 aluminium alloy track.
- ⊕ Grade 316 stainless steel slide bodies.
- ⊕ UV stabilised acetal sheaves.
- ⊕ Nylon slide liners.

TRACK FASTENINGS – 6mm (1/4") countersunk fasteners at 100mm (3 15/16") centres. **STOP HOLES** – 50mm (1 31/32") centres

PRODUCT No.	DESCRIPTION	LENGTH mm	M.W.L. kg	B.L. kg	WEIGHT g	LENGTH in	M.W.L. lb	B.L. lb	WEIGHT oz
Series 32 T-Track									
RC00476	Slide liners (pair), nylon, suits RC73201, RC73202, RC73243	107	-	-	7	4 7/32	-	-	0.3
RC00477	Slide liners (pair), nylon, suits RC73231	152	-	-	11	6	-	-	0.4
RC00478	Slide liners (pair), nylon, suits RC73234	107	-	-	7	4 7/32	-	-	0.3
RC7320-INS	Track bolt insulator	-	-	-	3	-	-	-	0.1
RC73201	Slide, loop top	102	1000 ^{*2}	2000 ^{*2}	185	4	2200 ^{*2}	4400 ^{*2}	6.5
RC73202	Slide, loop top, plunger stop	102	1000 ^{*2}	2000 ^{*2}	240	4	2200 ^{*2}	4400 ^{*2}	8.5
RC73231	Genoa car, 50mm (2") AP sheave, suits two 16mm (5/8") sheets, lock up/down plunger stop	146	1500	3000	480	5 3/4	3300	6600	17.0
RC73234	Genoa car, S60 BB Core Block™, suits 12mm (1/2") sheet, lock up/down plunger stop	104	1000	2000	400	4 1/8	2200	4400	14.1
RC73235	Genoa car, S45 BB Core Block™, suits 12mm (1/2") sheet, lock up/down plunger stop	104	700	1400	270	4 1/8	1540	3090	9.5
RC73243	Slide, spinnaker pole ring, plunger stop	102	-	-	315	4	-	-	11.1
RC73280	Track end, plastic	32	-	-	35	1 1/4	-	-	1.2
Track - Supplied with RC7320-INS nylon track bolt insulators									
RC7320-1.0 ^{*1}	Track, black	996	-	-	670	39 3/16	-	-	23.6
RC7320-1.5 ^{*1}	Track, black	1496	-	-	1000	58 7/8	-	-	35.3
RC7320-2.0 ^{*1}	Track, black	1996	-	-	1330	78 9/16	-	-	46.9
RC7320-3.0 ^{*1}	Track, black	2996	-	-	2000	117 15/16	-	-	70.5

*1 Silver track available - Order as RCxxxxxxS

*2 Load ratings based on pull perpendicular to track