

ULTRA LOW-LIGHT MARINE CAMERA

MODEL CRV-500C SKU C012800 UPC-A 811251020149

Nightwave is an ultra low-light camera built around SIONYX's patented Black Silicon CMOS sensor. It allows mariners of all levels to easily spot obstacles and debris in moonless starlight without white light or expensive thermal cameras — navigating safely, avoiding collisions, and maximizing time on the water. With easy mounting and setup, Nightwave can stream video to a mobile device via WiFi or directly connect to other hardware via analog output, displaying clear color digital night vision.

CONNECTED	Seamless integration with major brand MFDs via the analog video output. Convenient installation flexibility with built in WiFi video streaming and communication.
RUGGED	IP67 rated, submersible to 3 ft for 30 minutes. You can safely use Nightwave in inclement weather conditions.
CAPABLE	<1 MLX MOONLESS STARLIGHT sensitivity allows you to see well beyond human eyesight.
AWARE	44° field of view increases situational awareness to spot unexpected obstacles, debris, markers, vessels, and more.

CAMERA

SENSOR TYPE	XQE1350 BSI CMOS
RESOLUTION	1280 X 1024
FRAME RATE	60 HZ
HORIZONTAL FOV	44°
VISIBLE SPECTRUM	400-1200NM
FOCUS RANGE	10M TO INFINITY
LENS	16MM F/1.4

SYSTEM

VIDEO OUT	NTSC
VIDEO CONNECTION	SMA / BNC/ RCA
WIRELESS COMMUNICATIONS	WIFI + BLUETOOTH
POWER IN	12V DC
POWER CONNECTION	TINNED COPPER WIRE

ENVIRONMENTAL

INGRESS PROTECTION	IP67 WATER/DUST RESISTANT
SHOCK & VIBRATION	IEC60945 [V15G H:9G] IK08
OPERATING TEMPERATURE	-20°C TO +50°C
STORAGE TEMPERATURE	-20°C TO +80°C

RANGE PERFORMANCE	CLEAR WEATHER AT 1/4 MOON
DETECT MAN-SIZED OBJECT	150 M

All product, product specification, and data are subject to change without notice to improve reliability, function, design, or otherwise. Visit SIONYX.COM for up-to-date documentation.

PHYSICAL


WEIGHT	870 G [1.9 LBS]
DIMENSIONS	127 X 127 X 152 MM [5 X 5 X 6 IN]
MOUNTING OPTIONS	TRIPOD OR RAMMOUNT
	SINGLE 1/4" 20 CENTER MOUNT
	BULKHEAD MOUNT: 4 X M6 BLIND HOLES
	TOP-DOWN MOUNTING HOLES
MATERIAL	UV RESISTANT POLYCARBONATE

INCLUDED

BASE GASKET
MOUNTING HARDWARE
INSTALL TEMPLATE
USER MANUAL
-

EYESIGHT VS NIGHTWAVE





DEPTH: 127 MM | 5 IN







